MOBILE END DECK

UPRITE/BASE BRACKET LIMITATIONS

MOBILE GONDOLA UPRITE LIMITATIONS		
BASE BRACKET SIZE COMBINATION	MAXIMUM UPRITE HEIGHT	
13/13	NOT ALLOWED	
13/16	78	
13/19	90	
13/22	102	
13/25	114	
16/16	90	
16/19	102	
16/22	114	
16/25	120	
19/19	114	
19/22	120	
19/25	120	
22/22	120	
22/25	120	
25/25	120	

⁻For use with Low Base NOM 13-25 base brackets only.

PARTS LIST

ITEM	QTY	DESCRIPTION
1	2	3" CASTERS, LOCKING
2	2	1/2-13 HEX NUT
3	2	1/2" LOCKING WASHER
4	1	LH SPANNER
5	1	RH SPANNER
6	1	FRONT KICKPLATE
7	2	5/16-18 X 2 1/2 MS
8	2	5/16-18 HEX NUT
9	2	5/16 LOCK WASHER
10	2	3/8-16 X 4 HEX BOLT
11	2	3/8-16 HEX NUT
12	2	3/8 LOCK WASHER
13	2	END TRIM
14	4	#10 X 3/4 TEK SCREW
15	1	END DECK ASSEMBLY


IMPORTANT LOADING INFORMATION

- The maximum rated load for the Mobile Wall End Deck is 500 lbs evenly distributed
- To prevent tipping, do not move a loaded Mobile Gondola.

NOTE: Always use more than one person to assemble the Mobile Gondola system prior to adding the Mobile End Deck.



MOBILE END DECK



STEP 2. Attach item 1 to each of items 4 & 5 by inserting threaded stem of item 1 through large holes in items 4 & 5. Secure item 1 with items 2 & 3. (See Figure 2)

